


ST-510

UHF RFID Reader/Writer

-  **UHF** Frequency range from 862 to 955 MHz according to ETSI/EN 302208
-  Read range up to 7.5 m (tag dependent)
-  Trouble-free operation in harsh environmental conditions
-  Ready for Network operation
-  Shock resistant and solid construction for most demanding applications
-  Ideal for installation on forklift trucks or other mobile devices
-  Ideal for conveyor belts or access control
-  Weatherproof for indoor and outdoor use
-  CD ROM with demo software for PC to download data and database management



The Advanced ID standalone reader **ST510** is a robust, long range UHF RFID reader for outdoor and indoor use. It employs Advanced ID's state of the art technology that combines high performance and reliability with ease of use.

The **ST510** supports the tag protocol EPC C1 Gen 2. In addition, future protocols can be easily implemented. The integrated frequency hopping reduces the susceptibility and the mutual influence of the devices. The RFID reader can safely read up to 50 tags simultaneously.

The RFID reader/writer **ST510** operates together with a PC/laptop. The **ST510** is supplied with a USB connector providing both the voltage and the data exchange to the PC/laptop.

The **ST510** is ideal for all applications where fixed readers are required like in logistics, asset tracking, access control or warehouse management. Our development department can customize the RFID reader/writer for special applications. Contact us now!

ST-510

UHF RFID Reader/Writer



ADVANCED ID
ASIA ENGINEERING CO.,LTD.

PASSION FOR RFID

TECHNICAL SPECIFICATIONS

Read/write unit

Tag protocol:	EPC C1 Gen 2 (ISO 18000-6C)
Read range:	up to 7.5 m (tag dependent)
Write range:	70% of read range
Frequency range:	862-955 MHz (programmable for world-wide local regulation compliance, FCC Part 15 and ETSI 302208)
Polarization:	circular
RF power:	27 dBm up to 17 dB attenuation adjustable by software

Interface

PC interface:	USB (LAN, RS 485 and RS 232 on request)
---------------	---

Others

Power supply:	USB 5V 700 mA (with RS 485 and RS 232 external 9-12 VDC >1 A)
Operating temperature:	-20 ° to +50 ° C
Storage temperature:	-35 ° to +70 ° C
Humidity:	0-95% noncondensing
Protection class:	IP 64
Dimensions:	195 (W) x 155 (H) x 40 (D) mm
Weight:	600 g
Color:	orange, gray
Firmware:	simple firmware update through Software
Accessories:	CD ROM with control software, manual and drivers

Advanced ID Asia Engineering Co., LTD.

116 Moo 3 T. Maekhue, A. Doisaket
Chiangmai 50220
Thailand
Tel.: +66-53-387316-7
Fax: +66-53-387319
info@advancedidasia.com
www.advancedidasia.com

Your local contact: